





# **Product Specification Sheet**

**FC240 ResQ-WINDOW™** 

# Fire Curtain with up to 3-hour Fire Resistance featuring Vision Panel

### **KEY SPECIFICATIONS**

Headbox 1.2mm galvanized mild steel with 2mm

end caps

Rollers 76mm coated mild steel tube

**Motors** 24V DC


**Fabric** C41000WK

Bottom Bar 20mm x 20mm - 20mm x 40mm mild steel

Side Guides 100 x 50 rolled steel

**Electronics** See separate spec sheet

Vision Panel Silicone-coated fabric, size 375mm x 270mm



# **STANDARDS**

Tested and approved by Underwriters Laboratories LLC to Standards.

- UL10D: Fire Tests of Fire Protective Curtain Assemblies.
- UL1784: Air Leakage Tests of Door Assemblies and Other Opening Protectives.
- UL864: Control Units and Accessories for Fire Alarm Systems.

#### **DESIGNATIONS & SIZE LIMITATIONS**

Model	SIngle Roller	Multi Roller	Max Width (m)	Max Drop (m)	Classification	Test Standard	Certificate / Reports
FC240	Yes	Yes	45.0	12.0	120 mins fire rating in gypsum 180 mins fire rating in masonry	UL 10D UL 1784	20151020-R26410 20120808-R26410







### **HEADBOX SIZES**

The size of the curtain roller housing (headbox), depends on the curtain drop and width. Table 2 below gives details of the full range of headbox sizes for the FC240 fire protective curtains.

**Type A:** The standard headbox for use with curtain widths up to 5m.

Type B: Headbox for use with curtains up to 45m and limited installation height for headbox.

Type C: The standard headbox for use with curtain widths up to 45m.



## WARRANTY

A manufacturer's warranty is provided for a period of one year. Exclusions may apply if any element is sublet to an unauthorised party.

BLE Smoke & Fire Curtains, Unit 3 Holbrook Commerce Park, Holbrook Rise, Sheffield, England, S20 3FJ

Call: 0114 251 4703

Email: enquiries@blecurtains.com

Visit: www.ble-smokeandfirecurtains.com